

Wahoo Docks Captain's Chair - Top Mount

Assembly and Mounting Instructions



WHAT'S IN THE BOX

- a. (1) Chair Frame
- b. (2) Arm Rests
- c. (8) Arm Rest Mounting Bolts
3/16" x 1" Bolt/Locknut/Washers
- d. (1) Cup Holder
- e. (1) Fishing Rod Holder
- f. (4) Rod Holder Attachment Screws
3/4" Wood Screws
- g. (1) Pedestal Mount
- h. (4) Mounting Bolts
3/8" x 3 1/2" Bolt/Locknut/Washers

TOOL REQUIREMENTS

- (2) 9/16" Wrench
- (1) Power Drill
3/8" Drill Bit
- (1) Phillips Head Screwdriver
- (1) Clamp - optional



Bottom Detail
with Swivel Post

CHAIR ASSEMBLY

Attach Arm Rests (b) to Chair Frame (a) using the Arm Rest Mounting Bolts (c). Each Arm Rest can be attached on the left or right side depending on the desired location of the Cup Holder (d) or Fishing Rod Holder (e). After the arm rests are secure, slide the Cup Holder and Fishing Rod Holder into place, securing the Rod Holder with the Rod Holder Attachment Screws (f).

ATTACH MOUNTING BRACKET TO DOCK

Select a position on the dock where you'd like the Chair to be located. Position the Pedestal Mount (g) on the surface and drill four (4) 3/8" holes through the existing holes of the base of the Mount into surface. Preferably, the Mount will be secured through the dock surface into the frame of the dock to provide for a solid base. Once drilled, secure with Mounting Bolts (h) by placing a Flat Washer onto a Bolt, inserting the Bolt into one of the drilled holes and securing it on the back side with a Flat Washer and a Locknut. Repeat for each hole so that the Pedestal Mount is secured with four (4) bolts.



ATTACH CHAIR

Slide the swivel post located on the underside of the chair seat into the receiver at the top of the Pedestal.

Now your chair is ready!

We hope you enjoy it!

